

## IBC /TOTE TANK HEATERS

### Wet-area Wrap-around IBC / Tote Tank Heaters and Insulators (TOTEW | TOTEWI Series)

**NEW!**

- ▶ Extra-durable, water resistant design for outdoor/ indoor use and in wash-down environments
- ▶ Insulated, full-coverage design
- ▶ Heater has easy-to-program digital controller: Adjustable up to 140 °F (60 °C)
- ▶ Lightweight and easy-to-install with adjustable buckles
- ▶ Suitable for both metal and plastic IBC / Tote Tanks

#### Benefits:

- Ideal for a wide range of environments including outdoor and wash-down locations
- Even heat distribution and maximum energy efficiency
- Does not contaminate or scorch your product
- Easy-to-use — simple plug-and-play design
- Reusable and rugged — long service life
- Safe — heater has unique 360° grounded heating element and cool-touch surface for your safety



Heater — All-in-one, plug-and-play solution

*Image above shown with optional top cover (sold separately)*



Insulator — Pairs nicely with BriskHeat® IBC /Tote Tank Immersion Heater.

See [page 5-21](#)

*Image above shown with optional top cover (sold separately)*

**PLUG  
and  
PLAY**



**Water  
Resistant**



Easy-to-program digital controller



Adjustable Nylon Straps with Buckles

IBC /TOTE TANK HEATERS

**Wet-area Wrap-Around IBC/Tote Tank Heaters and Insulators**

(TOTEW | TOTEWI Series)

**Specifications:**

- Outer Material:** Extra-durable polyester cloth
- Insulation:** 0.5 in (13 mm) thick closed-cell neoprene
- Closure Method:** Adjustable straps with buckles
- Maximum Exposure Temperature:** 180°F (82°C)
- Height:** 36 in (914 mm), 42 in (1067 mm), or 48 in (1220 mm)
- Circumference:** Fits any vessel from 160 in (4064 mm) to 192 in (4877 mm)
- Ingress Protection Rating:** IP54

**Additional specifications for heater:**

- Operating Temperature:** Up to 140°F (60°C)
- Digital Control:** Programmable in °F and °C
- Built-in High-Limit Safety Thermostat:** 185°F (85°C)
- Heating Element:** 360° grounded heating element for your safety
- Dielectric Strength:** Over 2000 Volts
- Power Cord:** 6 ft (1.8 m) long
- 120 VAC: 3-prong grounded plug (NEMA 5-15P)
- 240 VAC: 3-prong grounded plug (NEMA 6-15P)



Heater (TOTEW series)

Insulator (TOTEWI series)



Optional Insulating Cover

**Ordering Information:**

**Heaters:**

| Part No. 120VAC | Part No. 240VAC | Height in (mm) | Capacity gal (l)      | Tank Perimeter Minimum in (mm) | Tank Perimeter Maximum in (mm) | Weight lbs (kg) |
|-----------------|-----------------|----------------|-----------------------|--------------------------------|--------------------------------|-----------------|
| TOTEW361-ADJV   | TOTEW362-ADJV   | 36 (914)       | 175 - 250 (640 - 950) | 160 (4060)                     | 192 (4880)                     | 19 (9)          |
| TOTEW421-ADJV   | TOTEW422-ADJV   | 42 (1067)      | 275 (1000)            | 160 (4060)                     | 192 (4880)                     | 23 (10)         |
| TOTEW481-ADJV   | TOTEW482-ADJV   | 48 (1220)      | 330 (1250)            | 160 (4060)                     | 192 (4880)                     | 26 (12)         |



Certified to UL safety standards Approval is for heater

**Insulators:**

| Part No.  | Height in (mm) | Capacity gal (l)      | Tank Perimeter Minimum in (mm) | Tank Perimeter Maximum in (mm) | Weight lbs (kg) |
|-----------|----------------|-----------------------|--------------------------------|--------------------------------|-----------------|
| TOTEW36IV | 36 (914)       | 175 - 250 (640 - 950) | 160 (4060)                     | 192 (4880)                     | 16 (7)          |
| TOTEW42IV | 42 (1067)      | 275 (1000)            | 160 (4060)                     | 192 (4880)                     | 20 (9)          |
| TOTEW48IV | 48 (1220)      | 330 (1250)            | 160 (4060)                     | 192 (4880)                     | 23 (11)         |

**Accessories:**

| Description                  | Part No.   |
|------------------------------|------------|
| Optional insulated top cover | TOTEW-TOPV |

Dimensions of top cover: 40 x 40 in (1016 x 1016 mm) with 4 in (102 mm) wide flaps. Flaps expand maximum dimensions to 48 x 48 in (1219 x 1219 mm)  
Insulation thickness of top cover: 0.25 in (6 mm)



**Your Support Office Locations:**

Batavia, IL - Rockford, IL - Waukesha, WI - Appleton, WI

Phone: 800-323-5712 | Fax: 630-406-0595

www.ashequipment.com | sales@ashequipment.com